



All for better networking.

4G06 N300 Wi-Fi 4G Volte Router



w w w.tendacn.com



4G06 N300 Wi-Fi 4G VoLTE Router

Tenda 4G06 is a VoLTE Router that integrates LTE and high-speed Ethernet uplink access, which provides users with flexible and diversified data access and Voice service .

Main Features



Wiring free Broadband access wherever you are

With LTE Advanced signal coverage for best performance and allows you to receive Internet access without cable and fiber ,it is the ideal choice for remote areas such as rural and suburban ,temporary store,holiday home ,giving devices ability to access to the Internet wherever and whenever the user is located.



High Quality Voice service

Based on the IP Multimedia Subsystem (IMS) network, with specific profiles for control and media planes of voice service on the LTE wireless broadband service.



Stronger and Wider Wi-Fi Signal

High power gain wireless signal 2.4 GHz band enlarge your Wi-Fi coverage, andBeamforming+ technology makes Wi-Fi signa l of 4G06 outstanding behind multiple walls.



Share your Wi-Fi up to 32 devices

Thanks to a powerful 880MHz and 28nm processor ,it shares the Wi-Fi up to 32 devicees base on dependable network.



Instantly access a mobile network with a Mini SIM card

Access a mobile network instantly just with an authorized Mini SIM cardr.

Specification ———

4G Cartgory	
4G/3G standards	LTE CAT.4
4G Mobile Bands	FDD LTE,TDD-LTE,WCDMA;
	4G FDD LTE:B2/B4/B5/B12/B13/B14/B66/B71;
	3G WCDMA:B2/B4/B5;
Max 4G+ speed	DL:150Mbps UL:50Mbps
Wi-Fi standards Wi-Fi	802.11b/g/n
frequency Wi-Fi	2.4GHz
speed Wi-Fi transmit	2.4GHz:300Mbps ;
Power	2.4GHz:up to 20dBm ; 1 × 10/100 Mbps LAN/WAN Port
	1 × 10/100 Mbps LAN Port
	1*Tel Port 1 × 2FF SIM Card Slot
Interface	Power on/off
	WPS/Reset
Button Antennas	
	2 detachable 4G/3G Antennas; 2 Internal Wi-Fi Antennas;
	Power
	Wi-Fi
LED indicators	LAN
	Internet 4G/3G Signal strength(3 Bars)
Dimensions (L*W*H)	185*126*60mm
Weight	About 350g
Power supply	Power adapter:lnput power AC 110V-220V 50/60Hz Output power:DC 12V==1A

Specification —

Software Specifications	
WAN Type	4G/3G or Wired Auto-APN Auto dial-up
4G/3G Features	Roaming SMS(Send/Receive/Delete) USSD Data limted PIN Management Broadcast and Hide Wi-Fi name Guest network Wi-Fi schedule
Wi-Fi functions	WEP,WPA-PSK, WPA2-PSK, WPA/WPA2
Wi-Fi security	
Software features	APP/Local/remote management Parental control DHCP(DHCP Server and Client) Virtual Server(UPnP/DMZ/Port Forwarding) DDNS(DynDns, 88ip) VPN(PPTP Client/L2TP Client/PPTP Server) Firewall QOS Upgrade firmware from local or OTA IPV4/IPV6 TR069
Certifications	
Working Environment	FCC Granted ROHS Granted PTCRB Granted (4G Moudule Only) GCF Granted (4G Moudule Only)
	On anything Transport way 0/00 40%C
Temperature	Operating Temperature: 0°C~40°C Storage Temperature: -30°C~70°C
Humidity Package lists	Operating Humidity: 10% ~ 90% RH Non-condensing Storage Humidity: 5% ~ 90% RH Non-condensing
Contents	1 * 4G VoLTE Router 1 * Ethernet cable 1 * Power adapter 1 * Phone cable 1 * Quick Installation Guide 2* SIM card adapter



SHENZHEN TENDA TECHNOLOGY CO.,LTD.

Tenda Technology Bldg.Int'IE-City, #1001 Zhong Shan Yuan Rd.,Nanshan District,Shenzhen China.

E-mail:support@tenda.com.cn Tel:+86-755-2765 7098 Fax:+86-755-2765 7178 PC: 5180 55



Specifications are subject to change without notice. Copyright ©2018 SHENZHEN TENDA TECHNOLOGY CO., LTD. All rights reserved. Tenda is the trademark of SHENZHEN TENDA TECHNOLOGY CO., LTD. All other brand names mentioned herein are the trademark or registered trademarks of their respective holders.